

Pavetuf

Priming Slurry



Priming Slurry

Guide to the Use & Installation

Priming Slurry

Pavetuf Priming Slurry is a polymer and cementitious Priming Slurry, specifically formulated to provide an exceptional bond between a new mortar base and all types of natural stone, concrete, clay, granite, marble, terracotta and porcelain paving.

- Quick & easy to install
- Simply mix with water
- 12m² coverage



Installation Guide

Tools & Equipment

- Paddle mixer
- A trowel, roller or paintbrush
- Mixing bucket
- Measuring Jug

Preparation

The paving elements should be cleaned and free from oils, grease, dust and loose particles by brushing or washing with water prior to the application of Pavetuf Priming Slurry.

Mixing

Measure 4.5 litres of clean water into the mixing bucket, then add all the contents to the water and mix for a minimum of 3 minutes until you have a liquid slurry base. The Priming Slurry is now ready to use.

Application

The backs of all paving elements should be primed to a thickness of 1mm - 2mm with a trowel, roller or paintbrush immediately prior to their placement upon the fine bedding concrete. The slurry needs to be wet when the paving units are placed on the bedding layer.



Technical

Pavetuf Priming Slurry is suitable for use in a variety of applications including driveways, paths, patios and commercial projects and should only be used with a bound/rigid construction. Paving should not be laid or primed if the temperature is below 5°C and falling. Temperatures of 3°C and rising is appropriate. The surface of the paving or substrate should not be frozen before priming and fresh primer should be protected from inclement weather until sufficient strength is achieved for damage not to occur.

The product can only be used on the day of mixing. It cannot be rejuvenated, so only mix what you need.

Specification

Workability: 1 Hour

Coverage: 12m² per 17kg tub (nominal coverage)

Adhesion: >2.N/mm²

Storage

Store unopened in a cool dry location away from extremes of temperature. When used within 12 months of the date of manufacture, the activity of reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement.

Health & Safety

Please ensure that appropriate PPE is used when preparing, mixing and applying this product.

Avoid skin and eye contact - wet cement can burn the skin.

Contains Portland Cement

Labelled in Accordance With (EC) No. 1272/2008

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause respiratory irritation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor/.

If skin irritation occurs: Get medical advice/attention.

Before use, please read the safety data sheet available at www.pavetuf.com

NOTE: The above notes are intended as a guide only and professional advice should be obtained before work is commissioned. Talasey Ltd does not offer nor imply any guarantees. It is your responsibility to ensure that you comply with all applicable health and safety legislation and guidelines.



DANGER

www.pavetuf.com

For further information or technical advice call
0330 333 8030

Distributed by Talasey Ltd
www.talasey.co.uk

TOTALLY TALASEY

TALASEY ARE PROUD TO BRING YOU THEIR EXTENSIVE PORTFOLIO OF THE FINEST LANDSCAPING PRODUCTS AND SOLUTIONS



Legal Notice - The information in this Document or on Talasey Ltd's Website referred to herein (the "Materials") is for guidance purposes and intended to assist you in your purchase and enjoyment of the product. Talasey Ltd will have no responsibility or liability, howsoever arising, for reliance on the information provided in the Materials. Talasey Ltd's sole liability in respect of any products shall be as outlined in the terms and conditions of purchase or in any express guarantee relating to the product purchased. Any product guarantee referenced in the Materials is subject to terms and conditions. Whilst we work closely with our partners, any arrangement you make or advice you take from them will be subject to your contract with them and Talasey Ltd has no liability in respect of any act or omission of any third party. Every effort has been taken to ensure that the information contained in the Materials is accurate, specifications and tolerances will be as contained in your order for the products, and may differ from those stated in the Materials, particularly with respect to natural materials where colours may differ from those illustrated. Guidance provided by Talasey Ltd is generic and advice should be sought in respect of local environmental and building regulations as applicable.



See website for terms & conditions
info@talasey.co.uk
0330 333 8030
www.talasey.co.uk




TALASEY
GROUP